

Fast, stylish, compact, flexible, versatile, brilliant

High resolution 2.5-inch display provides a clear view of critical details.

Exquisitely sharp photos even in candlelight or of moving objects thanks to the built-in optical image stabilizer and the high-sensitivity setting of up to ISO 1600.

Elegant and robust metal body available in black or silver finish.

The extended focal length range of the Leica wide-angle lens is equivalent to a 28-102 mm in the 35 mm format.

Elegance that’s more than skin deep The LEICA C-LUX 1 is an engagingly attractive companion with a fashionably compact form factor. Offered in smart black or lustrous silver and having a basic outline of only 5 x10 cm, it’s a camera you’ll want to take with you wherever you go. And its elegant exterior is complemented by cutting-edge technology : 6-megapixel capture, ultra short shutter delay, precise autofocus measurement, and a generous selection of scene modes make it ideal for taking great pictures effortlessly. Whether you’re on the beach, on a stroll through narrow streets, or in your favorite restaurant – the C-Lux 1 will capture all those precious moments you want to remember in stunning, true-to-life color and detail.

Camera	LEICA C-LUX 1
Image type/format	1/2.5" CCD sensor with 6.37 million pixels (6 m pixels effective in 4:3 format).
Resolution	In 4:3 format either 2816 x 2112, 2048 x 1536, 1280 x 960 or 640 x 480 pixels, 2816 x 2112, 2048 x 1536, 1600 x 1200 pixels. In Leica 3:2 format either 2816 x 1880 or 2048 x 1360 pixels. In 16:9 format either 2816 x 1584 or 1920 x 1080 pixels (corresponds to HDTV standard).
Video sequences	In 16:9 format with 848 x 480 ; in 4:3 format with 640 x 480 or in 4:3 format with 320 x 240 pixels at either 30 fps or 10 fps, duration of recording only limited by the capacity of the memory card. Recordings with sound.
Data recording	Data formats : Still pictures JPEG (Fine/Standard) ; Video QuickTime Motion JPEG.
Storage media	SD Memory Card and MultiMedia card (a 64 MB-SD card is supplied with the camera).
Film speed setting	Either automatic or manual ISO 80, ISO 100, ISO 200 or ISO 400 (in high sensitivity mode 800 – 1600).
White balance	Either automatic, for daylight, overcast sky, halogen light, two manual settings, fine adjustment of white balance in a range of –1500 to +1500K in 150 K steps (not available for automatic setting).
Lens	LEICA DC VARIO-ELMARIT f/2.8 – 5.6 / 4.6 – 16.8 ASPH. (corresponds to 28 – 102 mm in 35 mm format), 3.6 x optical zoom. Change of focal length by conveniently located zoom lever.
Optical image stabilizer	2 modes : either for exposure only or for exposure and monitor.
Focus range	Normal : 50 cm – infinity ; Macro/Simple/Motion Picture : wide-angle 5 cm/ telephoto 30 cm infinity.
Focusing	Autofocus, either normal or macro ; Autofocus modes/measurement range either 5 fields (full image area), faster autofocus with 3 fields (across the center) or with 1 central field, 1 field, or spot.
Exposure	Exposure modes either simple mode, normal image or macro. Exposure metering Multi-field measurement. Exposure bracketing ± 2 EV in 1/3 EV steps.
Series exposures	Either 3 fps or 2 fps at full resolution, max. 8 pictures with JPEG standard, max. 6 pictures with JPEG fine.
Shutter speed range	In fully automatic mode : 8 – 1/2000 sec. Starry sky mode : 15, 30, 60 sec.
Flash	Flash modes either automatic flash on with or without pre-flash (to combat red-eye), manual flash on (fill-in flash) with or without pre-flash, SLOW for slower shutter speeds (with pre-flash), flash off. Flash range (ISO set at Auto) 0.6 – 4.0 m (wide-angle), 0.3 – 2.0 m (telephoto), in high-sensitivity mode : 0.8 – 5.7 m (wide-angle), 0.8 – 2.8 m (telephoto). Flash exposure bracketing ±2 EV in 1/3 EV steps.
Scene modes	Portrait, soft skin, landscape, sport, night portrait, night landscape, self-portrait, food, party, candlelight, fireworks, starry sky, snow, baby1, baby2, high sensitivity.
Toning effects	Blueish, reddish, black and white or sepia.
LCD monitor	2.5" polycrystalline TFT color display with 207,000 pixels. Field of view : almost 100 % Power LCD mode, wide-angle viewing mode.
Self-timer	Either 2 s or 10 s countdown.
Power supply	Lithium ion battery, 3.7 V, 1150 mAh or optional mains unit.
Ports	USB 2.0 (Full speed), DC in (power supply) and AV out.
Printer compatibility	PictBridge
Battery capacity (approx.)	320 pictures (CIPA Standard)
Dimensions (W x H x D)	approx. 3 1/16 x 2 1/8 x 5/16 in
Weight	approx. 4.6 oz without battery and memory card ; approx. 5.6 oz with battery and SD memory card.
Scope of delivery	Battery charger, battery, 64 MB SD memory card AV cable, USB cable, AC cable, wrist strap, CD ROM with software (Adobe Photoshop Elements 4.0, Quicktime Movieplayer).
Accessories	
Case	real leather case with micro-velour lining. Cognac-brown Order No. 18 651 , Black Order No. 18 652 , Red Order No. 18 653
Direct mains connector	ACA-DC4 with mains cable (replacement)
Lithium-Ion-Battery	LEICA BP-DC4 (replacement)
Digital Adapter	Digital Adapter 2 for all Leica Televid Order No. 42 303



Illustrations in original size



LEICA C-LUX 1

